

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Panel PC, Box PC, Monitor**

with type designation(s)

S19A-QM87, S24A-QM87; SBOX-100-QM87; S19M-AD/PC, S24M-AD/PC

Issued to

**IEI Integration Corp.
New Taipei City, Taiwan**

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Location classes:**

Temperature	A
Humidity	B
Vibration	A
EMC	B
Enclosure	A

Issued at **Hamburg** on **2018-02-02**for **DNV GL**This Certificate is valid until **2023-01-29**.DNV GL local station: **Kaohsiung**Approval Engineer: **Dariusz Lesniewski**

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-024531-1**
Certificate No: **TAA00001CF**

Product description

Marine Panel PC Series : S19A-QM87 (with 19" LCD)
 : S24A-QM87 (with 24" LCD)
Power supply: 24 V DC (nominal)
Compass safe distance: 250 cm; 145 cm (steering)

Marine Embedded Box PC Series: SBOX-100-QM87
Power supply: 24 V DC (nominal)
Compass safe distance: 250 cm; 145 cm (steering)

Marine Monitor Series : S19M-AD/PC (19" LCD)
 : S24M-AD/PC (24" LCD)
Power supply: 24 V DC (nominal), 100-240 V AC / 50-60 Hz
Compass safe distance: 130 cm; 90 cm (steering)

Place of manufacture

ArmorLink SH Corp.
No. 515, Shenfu Rd., XinZhuang Industrial
Development Zone, Shanghai, P.R.C., 201108 China

Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Product certificate

If specified in the Rules, ref. Pt.4 Ch.9 Sec.1, the control and monitoring system in which the above listed hardware is used shall be delivered with a product certificate. For each such delivery the certification test is to be performed at the manufacturer of the application system before the system is shipped to the yard. The test shall be done according to an approved test program. After certification the clause for software control will be put into force.

Software control

All changes in software are to be recorded as long as the system is in use on board. Documentation of major changes is to be forwarded to DNV GL for evaluation and approval before implemented on board. Certification of modified functionality may be required for the particular vessel.

Application/Limitation

Marine Application Notes (DNVGL certification) in the user manuals to be observed:

- auto-dimming function is not covered by DNVGL certification
- touch-screen function is not covered by DNVGL certification
- desktop stand (DNVGL certified) to be used for installation of the Marine Panel PC and Marine Monitor
- not connected I/O ports need to be protected by protection caps (scope of delivery)

Type Approval documentation

Test Report: DELTA no. T220495, dated 2017-05-02

Test Report: INTERTEK no. 171200066TWN-001, dated 2017-12-07

Test Report: INTERTEK no. 170700108TWN-001, dated 2017-08-03

Data Sheets: S24A-QM87-2017-V11, SBOX-100-QM87-2016-V10, S19M-2016-V10

User Manual: S19A/S24A-QM87i-i5 Marine Panel PC, Rev. 1.00 – February 2, 2018

User Manual: S19M/S24M Marine Monitor, Rev. 1.00 – February 2, 2018

User Manual: SBOX-100-QM87i Fanless Marine Computer, Rev. 1.00 – February 02, 2018

Drawings:

- OutSide Dimension S-19A, dated 2015.07.08
- OutSide Dimension S-19M, dated 2015.01.28

Job Id: **262.1-024531-1**
Certificate No: **TAA00001CF**

- Outline Dimension S24A, dated 2014.06.26
- Outline Dimension S24M, dated 2014.06.27
- SBOX outside dimension SBOX-100-Qm87-R10, dated 2014.07.01
- VESA frame SXXM, dated 2018.08.28
- Back bracket(L) for SXXA S24A/S19Am dated 2017.08.22
- Back bracket(R) for SXXA S24A/S19Am dated 2017.08.22
- Drawing of display frame (no titled) dated 2013.12.11
- Lists of electronic components
- Diagram drawings of electronic boards

Software/Firmware Information Sheet

Type approval assessment report issued at Shanghai on 2017-02-10

Tests carried out

Applicable tests according to class guideline DNVGL-CG-0339, November 2016.

Applicable and selected tests according to IEC 60945, 4th edition (2002) as the following sections: 4.2.2.3, 5.2.2, 5.2.3, 8.2, 8.4, 8.7, 8.12, 9.2, 9.3, 10.3, 10.4, 10.5, 10.6, 10.7, 10.8, 10.9, 11.2.

Marking of product

The products to be marked with:

- manufacturer name
- model name / designation
- power supply ratings
- serial number

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed at least every second year and at renewal of this certificate.

END OF CERTIFICATE